



Berechnung des umbauten Raumes nach DIN 277

Geschoss	BGF R (m²)	BGF S (m²)	Definition	Höhe	BRI R (m³)
UG -01 (A)	2118,1		TG Allgemein	3,59	7.604,0
UG -01 (B)	51,1		TG Rampe	3,59	183,5
UG -01	2169,2				7787,5
EG -00 (A)	1981,7		EG Allgemein	3,81	7.544,2
EG -00 (B)	53,4		EG TG Rampe	3,15	168,2
EG -00 (C)	130,4		EG Kita MZR	4,34	566,1
EG -00		59,6	EG Sonderflächen		
EG -00	2165,5	59,6			8.278,5
OG +01 (A)	1483,2		OG Allgemein	3,00	4.445,0
OG +01 (B)	53,4		OG über TG Rampe	3,58	191,0
OG +01		276,6	OG Sonderflächen		
OG +01	1536,6	276,6			4.636,1
SG +02 (A)	1274,9		SG Allgemein	3,23	4.117,9
SG +02		270,7	SG Sonderflächen		
SG +02	1274,9	270,7			4.117,9

Unterirdisch	2.169,2	0,0		7.787,5
Oberirdisch	4.977,0	606,9		17.032,5
Ober- und Unterirdisch	7.146,2	606,9		24.820,0
BGF/BRI R + S	7.753,1 m²			24.820,0 m³

UNTERGESCHOSS**ERDGESCHOSS****OBERGESCHOSS****STAFFELGESCHOSS**